

cleaning systems in stainless steel series AM

technical datas

	pumps	basket diameter	inner height from	basket load from	filling capacity from	spraying pressure from	pump output from	pump motor	electric heating from	weight from
		mm	mm	kg	ltr.	bar	ltr./min.	kW	kW	kg
W 60 AM	1	600	370	100	50	1,8	80	0,5	2 / 3	130
W 80 AM	1	800	530	30 / 150	80	2,6	140	1,1	6	150
W 91 AM	1	900	530	200	130	3,1	160	1,5	8	190
W 92 AM	1	900	530	200	130	2 x 2,6	280	2 x 1,1	8	210
W 115 AM	1 / 2	1.150	720	300	200	2 x 3,0	360	2 x 1,5	10	320
W 150 AM	1 / 2	1.500	950	500	400	2 x 4,5	360	2 x 3,0	15	550
W 175 AM	2	1.750	1.000	750	600	2 x 4,5	480	2 x 4,0	2 x 10	750
W 200 AM	2	2.000	1.000	750	900	2 x 5,5	800	2 x 5,5	30	1.400
W 250 AM	2	2.500	1.150	1.500	1.250	2 x 7,5	900	2 x 7,5	45	2.200
W 300 AM	2	3.000	1.300	2.000	1.800	2 x 7,5	1.000	2 x 7,5	60	2.900

temperature up to 95°C
voltage 400/230/24 V
washing time 0 - 30/60/120 min.



W/K 150 AM



series AM cleaning systems in stainless steel



Georg Render GmbH
Reinigungsanlagen

Georg Render GmbH
Reinigungsanlagen

Sölterstr. 31 ■ 32107 Bad Salzflöten
Tel. 05208.6595 ■ Fax 05208.6570

■ info@render-gmbh.de
■ www.render-gmbh.de

Sölterstr. 31 ■ 32107 Bad Salzflöten
Tel. 05208.6595 ■ Fax 05208.6570

■ info@render-gmbh.de
■ www.render-gmbh.de

cleaning systems in stainless steel series AM

The series AM is a modified version of the standard series W/K as combined machine for automatic and manual cleaning.

These cleaning machines were especially developed for the use in repair and maintenance range and for the treatment, preparation and postprocessing of particularly complicated parts geometries.

The AM-version is available from type 60 on.



Cleaning machines of the AM-series are based on the serial machines, fitted with the following additional components:

- cover with window, lighting and gloves
- pump for hand pistol ca. 3 - 6 bar with high liter capacity (e. g. for pressure rinsing of oil channels and pipes in crankshafts or motor blocks etc.)
- washing brush, medium-flooded
- blow off pistol compressed air
- shiftable and removable perforated sheet device (at type W/K 80 AM) optional
- high pressure pump 100 bar / 160 bar for removal of persistend dirt (e. g. oil coal)



high pressure pump



shiftable and removable perforated sheet device (at type W/K 80 AM), optional with cleaning tub

W/K 80 AM

From machine size 91/92 AM on the manual parts cleaning happens directly on the turn table washing basket.

Gladly we make you a specified offer - let us advise you !

Georg Render
Reinigungsanlagen

cleaning systems in stainless steel series AM



W/K 60 AM

All of the machines could be used in warm/watery range (series W) as well as in a special version with cold cleaning agents/solvents (series K), if needed also in an explosion-proofed version.

Due to the manual access and the related EU-norms the loading heights of the different machine types will increase.



W/K 92 AM



W/K 115 AM

with extractable basket and transport system (optional)



W 80 AM/C

turning device

On the basis of the machine version AM further combinations with components of other series are possible.

E. g. these machines could additionally be fitted with a turning device (series C) to cover also wide spreaded spectra of parts.

Gladly we make you a specified offer - let us advise you !

Georg Render
Reinigungsanlagen

Sölterstr. 31 ■ 32107 Bad Salzufen
Tel. 05208.6595 ■ Fax 05208.6570

■ info@render-gmbh.de
■ www.render-gmbh.de